

WINTEC

Smart POS, Smarter Retail

ACS-S100



Snack Shop



Fresh Market



Convenience
Store



Supermarket



Intergrated with dual display, touch screen, label printer, AI camera



FHD display, PCAP touch screen
Multiple screen sizes for different scenarios



Solid and reliable metal platform



Optional AI camera
Fast and accurate product identification



High performance label printer
adapts to high frequency use



Waterproof, insectproof
and dustproof design for
harsh scenarios



ACS-S100 Specification



CPU

J6412 Quad Core 2.0GHz
i3-1115G4 Dual Core 3.0GHz
i5-1135G7 Quad Core 2.4GHz



Memory

4GB, up to 32GB



Storage

128GB, up to 512GB



Printer

60mm Label printer



Main Display

15.6" LCD,
1920*1080/ 1366*768 (PCAP)



2nd Display(Optional)

11.6" LCD, 1366*768
(PCAP, optional)
15.6" LCD, 1920*1080/ 1366*768
(PCAP, optional)



WiFi&BT(Optional)

802.11 b/g/n/ac + BT4.2



OS

Win10,
Linux (V20.4 and above)



Ethernet

1*10/100/1000M



Scale

Capacity&Division 6/15kg 2/5g
Capacity&Division 15/30kg 5/10g



Interfaces

4*USB, 2*RS232(RJ48), 1*RJ45,
1*DK, 1*24V IN, 1*HDMI



Dimension

360*380*595 (mm)



Power Adapter

AC Input 100~240V, 50-60Hz
DC Output 24V/2.5A



Options

MSR, RFID, AI camera



Platter Size

380*283 (mm)



Speaker

1*5W Speaker

ACS-S100 Specification



Android



CPU

RK3568 Quad Core 2.0GHz



Memory

4GB



Storage

32GB



Printer

60mm Label printer



Main Display

15.6" LCD,
1920*1080/ 1366*768 (PCAP)



2nd Display(Optional)

11.6" LCD, 1366*768
(PCAP, optional)
15.6" LCD, 1920*1080/ 1366*768
(PCAP, optional)



Scale

Capacity&Division 6/15kg 2/5g
Capacity&Division 15/30kg 5/10g



OS

Android 11



Ethernet

1*10/100/1000M



WiFi&BT

802.11 b/g/n/ac + BT4.2



Interfaces

4*USB, 2*RS232(RJ48), 1*RJ45,
1*DK, 1*24V IN, 1*HDMI, 1*OTG



Dimension

360*380*595 (mm)



Power Adapter

AC Input 100~240V, 50-60Hz
DC Output 24V/2.5A



Options

MSR, RFID, AI camera



Platter Size

380*283 (mm)



Speaker

1*5W Speaker